




CEILING RADIATION DAMPER WITH REGISTER BOX ASSEMBLY



MODEL:
CRD50-NI-BT-26GS
CRD50-NI-BT-26GS-EA



APPLICATION

Model CRD50-NI-BT-26GS/ CRD50-NI-BT-26GS-EA is an 1-Hour rated damper and box assembly. The damper is UL fire rated for Ceiling/Floor and Ceiling/Roof Assemblies L528, L558, L562, L563, L574, L585, M562, P533, P544, P545, P547, and P580. Contact us for additional applicable Ceiling/Floor and Ceiling/Roof Assemblies.

TYPE CRD: Rectangular damper with non-insulated galvanized steel register box



1/2\"/>

CEILING RADIATION DAMPER


- Rating: UL listed ceiling radiation damper UL-555C
- Fusible Link: 165°F standard
- Blades: 22 Ga. galvanized steel
Ceramic Fiberglass Cover (for total blade area > 80 sq. in.)
- Frame: Roll formed 22 Ga. galvanized steel

PLENUM BOX

- Outer Box: 26 Ga. galvanized steel
- Collar: Roll formed 26 Ga. galvanized steel with roll formed 1/4\"/>
- Insulation: None provided
- Round beaded collar provided to nominal diameter order sizes (1-1/4\"/>

NOTES:

- Available in stainless steel.
- Manufactured with blades open as shown.
- Minimum CRD50-EA-NI-BT register sizes not less than 6\"/>
- Ceramic insulation is not required on dampers with areas less than 80 SQ/IN and is optional. Dampers above 80 SQ/IN will be provided with blade insulation.
- Register/Grille supplied by other.



"D" = 5" + COLLAR DIA.

Minimum Size (WxH)	Maximum Size (WxH)
6" x 6" x 3" (collar)	24" x 24" x 22" (collar)

